

Cherwell 21 Round 38cm Under-countertop Washbasin, Overflow

ILLUSTRATED

- S2687** Cherwell 21 Round 38cm under-countertop washbasin with overflow
- A4852** Sensorflow 21 compact washbasin mounted spout with integral sensor, 3.7 litre per minute aerated spray outlet, combined inlet servicing valve and filter, mains
- S8722** Waste 1¼" brass strainer waste, 80mm slotted tail
- S8920** Trap 1¼" plastic resealing bottle, 75mm seal, multi-purpose outlet

OPTIONS

- A4851** Sensorflow 21 compact washbasin mounted spout integral sensor servicing valve and filter, copper tube inlets, battery
- A4853** Sensorflow 21 compact washbasin mounted spout with integral sensor, 3.7 litre per minute aerated spray outlet, combined inline servicing valve and filter, link

ILLUSTRATED PRODUCT DETAILS

Sizes

S2687 w:400 x d:400

Weights

S2687 5.05 KG

A4852 1.60 KG

S8722 0.22 KG

S8920 2.00 KG

Materials

S2687 Fine Fireclay

A4852 Chrome Plated Brass

S8722 Chrome Plated Metal

S8920 Plastic

Finishes

S2687  White (01)

A4852  Chrome (AA)

S8722  Chrome (AA)

S8920  Neutral / No Finish (67)

Capacity

S2687 3.0 litres

Flow rates

A4852 3.7 Litres per minute @ 3 bar pressure

Designer

Robin Levien, RDI

FINISH OPTIONS

 (AA) Chrome

 (GN) Ultra Steel

Standards

Washbasin to BS EN 14688 & BS EN 31

Special Notes

This washbasin is not suitable for separate pillar taps. Washbasin mounted on underside of countertop using fixing clips provided. Joint sealed using waterproof sealant (not supplied).

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900AA

E: info@idealspec.co.uk | T: 0870 122 8822 | F: 0870 122 8282 | www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

